



Тип	Диаметр Внешняя Ширина Ширина Радиус					Номинальная нагрузка (N)		Максимальная скорость	
	Диаметр Диаметр		B	B1	Rs	Динамический	Статический	Смазка	Нефть
	D (мм)	D (мм)	Мм	Мм	(Мм)				
6916	80	110	16	16	1	25000	24000	5.70	6.80
6915	75	105	16	16	1	24400	22600	6.10	7.20
6914	70	100	16	16	1	23700	21200	6.40	7.60
6912	60	85	13	13	1	20200	17300	7.50	8.90
6913	65	90	13	13	1	17400	16100	7.10	8.40
6911	55	80	13	13	1	16600	14100	8.10	9.60
6910	50	72	12	12	0.60	14540	11710	9	11
6909	45	68	12	12	0.60	14100	10830	9.70	11
6908	40	62	12	12	0.60	13678	9968	11	13
6907	35	55	10	10	0.60	10900	7818	12	14
6906	30	47	9	9	0.30	7242	5003	14	17
6905	25	42	9	9	0.30	7001	4540	16	19
6904	20	37	9	9	0.30	6381	3682	19	23
6903	17	30	7	7	0.30	4588	2565	23	38
6902	15	28	7	7	0.30	4321	2259	26	30
6901	12	24	6	6	0.30	2886	1466	31	36
6900	10	22	6	6	0.30	2695	1273	34	41
699	9	20	6	6	0.30	2467	1081	34	40
698	8	19	6	6	0.30	2237	917	36	43
697	7	17	5	5	0.30	1605	719	36	43
696	6	15	5	5	0.15	1340	523	40	45